

**Section** \_\_\_\_\_

HV Outer sheath

**Application** \_\_\_\_\_

Field

Laboratory



**PRODUCT BENEFITS**

**TOOL CAPACITY**

**Diameter** 95 - 145 mm  
3,740 - 5,709 inch

**Thickness capacity** 11 mm / 0,433 in

**Shield detection** No

**TOOL DIMENSIONS**

**Length** 280 mm

**Width** 180 mm

**Height** 360 mm

**Weight without box** 5,2 Kg

**Packaging** Case

## Stripping tool for HV and EHV cable's outer sheath and shield

**TO DO WHAT**

The DM 95-145 enables the user to remove the outer sheath and the aluminium/lead shield on HV and EHV cable by successively performing a longitudinal and circular cut



**Spare part**

LDMS38 - Spare blade for outer sheath and shield

**Associated tool**

- EGA - HV and EHV cable's outer sheath and shield spreaders
- EV-HTB - HV and EHV cable's outer sheath and shield splitters
- EVP - HV and EHV cable's lead sheath splitters

**ALROC SAS**

Z.I. de la Fonderie - 72160 TUFFE  
FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

HV cables Tools

# DM 95-145



Part Number	Diameter	Tool capacity		Dimensions			Packaging
		Thickness capacity	Shield detection	Length	Width	Height	
DM 50-95	50 - 95 mm 1,969 - 3,740 in	7 mm / 0,276 in	No	260 mm 10,236 in	160 mm 6,299 in	320 mm 12,598 in	case
<b>DM 95-145</b>	<b>95 - 145 mm 3,740 - 5,709 in</b>	<b>11 mm / 0,433 in</b>	<b>No</b>	<b>280 mm 11,024 in</b>	<b>180 mm 7,087 in</b>	<b>360 mm 14,173 in</b>	<b>case</b>
DMS 50-95	50 - 95 mm 1,969 - 3,740 in	7 mm / 0,276 in	Yes	260 mm 10,236 in	160 mm 6,299 in	320 mm 12,598 in	case
DMS 95-145	95 - 145 mm 3,740 - 5,709 in	11 mm / 0,433 in	Yes	280 mm 11,024 in	180 mm 7,087 in	360 mm 14,173 in	case