

**Certifications**

Approved by ENEDIS

**Section**

MV Semi-conductor

**Application**Field  
Laboratory**PRODUCT BENEFITS**

Tool preset in factory safer than glass

**TOOL CAPACITY**

|                 |                                   |
|-----------------|-----------------------------------|
| <b>Diameter</b> | 15 - 240 mm<br>0,591 - 9,449 inch |
|-----------------|-----------------------------------|

**TOOL DIMENSIONS**

|                           |         |
|---------------------------|---------|
| <b>Length</b>             | 250 mm  |
| <b>Width</b>              | 40 mm   |
| <b>Height</b>             | 25 mm   |
| <b>Weight without box</b> | 0,19 Kg |
| <b>Packaging</b>          | Box     |

**ALROC SAS**Z.I. de la Fonderie - 72160 TUFFE  
FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

## Scraper for residues of bonded semiconductor screen.

**TO DO WHAT**

The tool GRI enables the user to remove bonded semiconductor screen residus.

**Options**

EGR - Pouch for GRI

**Spare part**

LGR - Spare balde scrape semiconductor

**Associated tool**

CWB/18-60-FEP - Tool to remove bonded semiconductor with chamfer on the semiconductor cutback

BRMRD1E - Tool to remove insulation

MV cables Tools

**GRI**



| Part Number | Diameter                        | Tool capacity | Dimensions         |                   |                   | Packaging |
|-------------|---------------------------------|---------------|--------------------|-------------------|-------------------|-----------|
|             |                                 |               | Length             | Width             | Height            |           |
| <b>GRI</b>  | 15 - 240 mm<br>0,591 - 9,449 in |               | 250 mm<br>9,843 in | 40 mm<br>1,575 in | 25 mm<br>0,984 in | box       |