

IMS III

intercable
TOOLS

CABLE STRIPPER FOR PRIMARY INSULATIONS FOR MV/HV CABLES WITHOUT SILICON

Handling

Shift lever for activation/
deactivation of the axial feed
enables an optimal guidance
and precise circular cut

Agility

Movable roller system adapts
optimally to small and large
diameters, no silicon required

Precision

Smooth blade grind and
adjustable cutting depth
ensures a surface on the
smooth primary insulation

Range

Application range
for MV-cables up to
1.000 mm² / 15-58 mm Ø

High quality

Light and robust design
through the use of light
metals and stainless INOX



www.intercable-tools.com





TECHNICAL CHARACTERISTICS

Designed to remove the primary insulation layer of MV/HV-cables from 6-45 kV and an insulation thickness up to 15mm and a dimension up to 1.000mm² and 15-58 mm Ø

- Light and robust design through the usage of light metals and stainless INOX
 - Positioning on the cable like a vice system
 - Spiral and round cut
 - Optimal sliding properties thanks to the movable wheel system, **no additional silicon required**
 - Axial feed activation/deactivation with 2-speed advance possibility
 - Replacable blade, made of hardened steel
 - Adjustable blade depth from 0 to 1,5mm (each klick = 0,1 mm)
- Dimensions/Tools: 220x60x90 mm
 - Weight/Tool: 580 gr.



SET EQUIPMENT & ACCESSORIES

Set 17260:

- IMS III - cable stripper 17261
 - 2,5 mm Allen wrench 17100
 - Soft nylon case AB6230
- Spare blade 17232

