

Section

MV Semi-conductor

ApplicationField
Laboratory**PRODUCT BENEFITS**

No silicon needed
 Fine tuning of the blade with a 'click' for each 1/10 mm
 Very smooth finish over the insulation
 Adjustable length of semiconductor cutback : 25-30-40 mm / 0,984-1,181-1,575 in

TOOL CAPACITY

| | |
|--|---------------------------------------|
| Diameter | 18 - 60 mm 0,709 - 2,362 inch |
| Thickness capacity | 1,8 mm / 0,071 in |
| Angle of the chamfer on the semiconductor | 13° |
| Remaining length of the semiconductor | 25-30-40 mm / 0,984-1,181-1,575 in |

TOOL DIMENSIONS

| | |
|---------------------------|---------|
| Length | 235 mm |
| Width | 125 mm |
| Height | 90 mm |
| Weight without box | 0,85 Kg |
| Packaging | Box |

ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE
 FRANCE
 Phone: +33 2 43 71 11 80
 Fax number : +33 2 43 71 16 51
 www.alroc.fr

Tool to remove bonded semiconductor with chamfer on the semiconductor cutback

TO DO WHAT

The CWB/18-60-FEP enables the user to easily remove the bonded semi-conductor with a chamfer on the transition, leaving a very smooth finish over the insulation
 The CWB 18-60 works without silicone

**Options**

SGM - Large size pouch

Spare part

LCWB-FEP - Spare blade for bonded semiconductor with chamfer 13°

LCWB-FEP-V - Spare blade for bonded semiconductor with chamfer 13° + screw

Associated tool

GRI-RTE - Scraper for residues of bonded semiconductor screen with protection pouch

PG3HTA/2530 - Pliers for MV cables outer sheath

BRMRD1E - Tool to remove insulation

MV cables Tools

CWB/18-60-FEP



| Part Number | Diameter | Tool capacity | | | Dimensions | | | Packaging |
|----------------------|--------------------------------|--------------------|---|---------------------------------------|--------------------|--------------------|-------------------|-----------|
| | | Thickness capacity | Angle of the chamfer on the semiconductor | Remaining length of the semiconductor | Length | Width | Height | |
| CWB/18-60 | 18 - 60 mm 0,709 - 2,362 in | 1,1 mm / 0,043 in | 8° | 25-30-40 mm / 0,984-1,181-1,575 in | 235 mm 9,252 in | 125 mm 4,921 in | 90 mm 3,543 in | none |
| CWB/18-60-FEP | 18 - 60 mm 0,709 - 2,362 in | 1,8 mm / 0,071 in | 13° | 25-30-40 mm / 0,984-1,181-1,575 in | 235 mm 9,252 in | 125 mm 4,921 in | 90 mm 3,543 in | box |
| CWB/18-60-MVS | 18 - 60 mm 0,709 - 2,362 in | 1,1 mm / 0,043 in | 13 ° | With MVS stop | 235 mm 9,252 in | 125 mm 4,921 in | 90 mm 3,543 in | box |