

Section

HV Semi-conductor

Application

Field



PRODUCT BENEFITS

Back-iron to set the pitch of the tool in order to get a good result over the insulation

TOOL CAPACITY

Diameter 100 - 140 mm
3,937 - 5,512 inch

Max cutting depth 8 mm / 0,315 in

TOOL DIMENSIONS

Length 730 mm

Width 195 mm

Height 115 mm

Weight without box 6,5 Kg

Packaging None


ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE
FRANCE
Phone: +33 2 43 71 11 80
Fax number : +33 2 43 71 16 51
www.alroc.fr

Monofuncton tool for bonded semiconductor

TO DO WHAT

The LHS5 enables the user to remove bonded semiconductor



Spare part

LASC5 - Spare blade for bonded semiconductor

Associated tool

LH5 - Monofunction tool for insulation

DM 95-145 - Stripping tool for HV and EHV cable's outer sheath and shield

BMFD/55-160 - Thrust to stop the tool

HV cables Tools

LHS5



Part Number	Diameter	Tool capacity	Dimensions			Packaging
		Max cutting depth	Length	Width	Height	
LHS2	38 - 60 mm 1,496 - 2,362 in	5 mm / 0,197 in	425 mm 16,732 in	105 mm 4,134 in	85 mm 3,346 in	none
LHS3	60 - 80 mm 2,362 - 3,150 in	10 mm / 0,394 in	460 mm 18,110 in	130 mm 5,118 in	85 mm 3,346 in	none
LHS4	80 - 110 mm 3,150 - 4,331 in	12 mm / 0,473 in	640 mm 25,197 in	155 mm 6,102 in	95 mm 3,740 in	none
LHS5	100 - 140 mm 3,937 - 5,512 in	8 mm / 0,315 in	730 mm 28,740 in	195 mm 7,677 in	115 mm 4,528 in	none